



- Eliminates odors & improves Indoor Air Quality
- Unique self-feeding package installs in air handler or return duct
- A true odor neutralizer – not an odor mask or cover-up
- Residential HVAC Odor Block treats up to 3 ton systems for 2 months
- Residential HVAC Odor Block XL treats 2500 square feet for 6 months
- Commercial HVAC Odor Block treats 10 to 15 ton systems for 4 months

Description

ClenAir HVAC Odor Block is not a perfume mask or cover-up. The unique ClenAir formula molecularly reacts with the airborne odor-causing compounds and eliminates them and other indoor pollutants leaving clean, fresh, air behind. The HVAC Odor Block makes it easy to remove odors and improve the indoor air quality in the entire home or building by treating the air through the HVAC system.

Eliminates odors caused by mold, mildew, bacteria, pets, smoke, musty odors, water damage, fire damage, paints, chemicals, animal decay, stale air, garbage areas, sewer gases, skunks, and more!

Application

Use in A/C units, furnaces, rooftop units, fan coil units, and air handlers. Residential HVAC Odor Block treats up to 3 ton systems for 2 months and the XL will treat up to 2500 square feet for 6 months. Commercial HVAC Odor Block treats 10 to 15 ton systems for 4 months.

Packaging

	Nu-Calgon #	ClenAir #
Residential HVAC Odor Block	61060	1502
Residential HVAC Odor Block XL	61070	
Commercial HVAC Odor Block	61061	CA1015

Odor Neutralizers

HVAC Odor Block



Directions

Residential HVAC Odor Block - 61060

1. Carefully open the box top and remove the plastic wrapped Odor Block from the box.
2. Put the bare Odor Block back into the box.
3. Secure or place the Odor Block box on or near the air filter, in the blower compartment or any other accessible place in the return duct system. The specially vented box will allow the Odor Block to slowly evaporate into the HVAC system treating all of the system air. For faster treatment or severe odors, the box top can be left open or ajar.
4. When the Odor Block is completely shrunk or dried, it is time to replace it with a new Odor Block. Lasts up to two months.

See Back Page for Additional Package Size Directions.



Residential HVAC Odor Block XL - 61070

1. To activate, use utility knife to cut away inside plastic from oval vents on each side of the box. The product stays in the box.
2. Place odor block package in the blower compartment or anywhere there is access to the return duct work. For faster treatment or severe odors, open the box top and remove the entire block in plastic from the box. Remove the plastic and place the bare block back into the box and close the top. Place odor block in the return duct or blower compartment.
3. Replace after 6 months.

Commercial HVAC Odor Block - 61061

1. Carefully peel away the top of the label to expose the vent openings. Then, peel off the two lower side labels to activate the Carbon Z filtration.
2. Place the Odor Block box in the air handler or other convenient place in the return duct system. Be sure to place the pail so the carbon opening are in the direction of the airflow. The Odor Block will slowly evaporate into the HVAC system treating all of the building air.
3. When the Odor Block is completely shrunk or dried, it is time to replace it with a new Odor Block. Lasts up to four months.