

CCD110 Refrigerant Charging Scale

ACCURATE. PRECISE. RELIABLE.

The most trusted brand of refrigerant charging scales.

FEATURES:

- Weigh, charge or recover refrigerants up to 110 lb (50 kg)
- 0.20 oz (5 g) display resolution
- · Accurate to 0.015% of reading
- Battery/Life: One 9V = 75 hrs; Two 9V:
 = 150 hrs
- 3 button corded control with large, high contrast, wide angle, display
- · Cast aluminum platform and base
- 3 point non-rocking foot pattern for best stability
- Heavy duty rubber platform mat
- · Unique patent pending design



Accepts wide range of tank sizes



Padded soft case with embroidered front



Ergonomic control with large display



COMPUTE-A-CHARGE® *CCD110 Refrigerant Charging Scale*



CCD110 SPECIFICATIONS

Weight Capacity	110 lb (50 Kg)
Weight Accuracy	0.015% of Reading [or \pm 0.2 Oz (5 g) whichever >]
Display Resolution (Increments)	0.20 Oz (5 g)
Continuous Battery Life (APO DISABLED)	Up To 75 Hrs (One 9V Alkaline); Up To 150 Hrs (If 2nd 9V)
Platform Dimensions	"Delta" Shape [fits w/l 10.4" (26.4 cm) circle]
Control Type	Handheld LCD Display
Keypad	3 Button (On/Off, Lb/Kg, Tare)
Control to Scale Connection	6'(1.8 m) Flexcord, Extended
Auto Power Off Feature (ENABLED)	Display shows "APO ON" at power up. [Display will turn OFF after 10 minutes inactivity]
Auto Power Off Feature (DISABLED)	Display shows "APO OFF" at power up [Display will be constant ON]
Smart Awake	Yes (Displays weight at time of Auto-Off)
Power Source	(1 or 2) 9V Alkaline (1 Included)
Unit Weight	5.5 Lbs (With Case) 4.3 Lb Scale Only
Weight Readout	Selectable (Lb & Oz, or Kg & Gm)
360 Degree Hanger Hook	Yes
Rubber Platform Cover	Yes (Replaceable)
Carry Case	Fabric case with zipper, front/back padding and internal pocket
Overload Protection	Mechanical and visual
Battery Level Indicator	3 Segment symbol
Operating Temperature Range	14°F to 122°F (-10°C to 50°C)
Approvals	CE (Commonwealth Europe)
Calibration	To National Institute Of Standards & Technology (U.S.)
Scale Packaging	Color sleeve (with key features and scale specifications)
Warranty	1 Year